

LCD indicator

LCD indicator with lithium-ion rechargeable battery, 8 hours of intensive usage with a single charge



FEATURES:

- ABS or Stainless steel housing.
- IP65 protection.
- LCD display with 6 digits of 40 mm.
- Wall support included.
- Battery charger AC/DC 100-240 Vac 50-60 Hz
- Internal battery Lithium-ion rechargeable 7,2 V/ 2.6 Ah. 8 hours of intensive usage with a single charge.
- 2 output RS232 are included.
- Unique range, multi-range ou multi-interval.
- Units: kg.
- Approval 6.000 divisions OIML class III and IV.
- EC approval.

KEYBOARD FUNCTIONS:


- Back to menu / Mode, Zero / Untare, Gross / Net, Tare, Weighing total / Exit, Switch on / Off, Print / Manual sending of weight / Units.

FUNCTIONS:

- Weight accumulation: automatic / manual
- Totalization on screen
- Gross / Net
- Manual tare and pretare
- Back to zero
- Piece counting function
- Checkweigher function with a visual value alarm
- Function division 1/10 verification. Display for a few seconds



SET A TARGET AND TOP/BOTTOM MARGIN PARAMETERS



With a visual value alarm

Code #	Description
210227	ABS GI400 BAT LI ION LCD indicator IP65 protection
210228	Stainless steel GI400 BAT LI ION LCD Indicator with IP65 protection
Accessories	
Code #	Accessories description
220002	RS485 output
220008	Additional memory ALIBI/DSD
220027	Communication board – Wifi (1)

(1) Wifi communication board is under development (not available).